

# Material Safety Data Sheet

Page 1 of 5

Material Name: Accura<sup>®</sup> e-Stone<sup>™</sup>

## I. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

**Product/Trade Name:** Accura<sup>®</sup> e-Stone<sup>™</sup> (green and peach)  
**System/Laser Compatibility:** For SLA<sup>®</sup> systems equipped with solid-state (Nd:YVO<sub>4</sub>) lasers  
**Chemical Family:** Epoxy resin containing reactive diluent  
**Product Use:** Material for SLA series stereolithography systems.  
**Manufacturer:**

### Hazardous Materials Identification System (HMIS):

(Degree of hazard: 0 = low, 4 = extreme):

Health 2  
Flammability 1  
Physical Hazards 1

### Personal Protection:

Skin, eye protection



Manufacturer Contact	3D Systems, Inc. 333 Three D Systems Circle Rock Hill, South Carolina U.S.A.
For Information	Phone: 803.326.3900 or Toll-free Phone: 800.793.3669
Emergency	800.424.9300 - Chemtrec

## II. COMPOSITION INFORMATION

CAS #	Component	Percent
16096-31-4	1,6-bis(2,3-epoxypropoxy)hexane	10% – 25%
Mixture 108-32-7, 89452-37-9, 71449-78-01	Mixture containing triarylsulfonium salt 50% Propylene Carbonate 50% Mixed triarylsulfonium hexafluoroantimonate salts	1% – 5%

### Product Information

This product is considered to be hazardous (irritant, sensitizer) according to 29CFR 1910.1200 (Hazard Communication Standard).

## III. HAZARDS IDENTIFICATION

### Emergency Overview

This material is an irritant. Causes eye irritation. Causes skin irritation. Can cause allergic skin reaction. Toxic to aquatic organisms. Do not release to the aquatic environment. Hazardous polymerization can occur upon depletion of inhibitor or exposure to heat or UV light.

### Potential Health Effects:

Eyes: Can cause irritation consisting of redness, swelling and pain.  
Skin: Can cause irritation or other allergic reactions, including redness and/or swelling.  
Inhalation: Inhalation causes respiratory irritation.  
Ingestion: Ingestion can cause nausea, diarrhea and/or stomach pain.  
Chronic: Can cause an allergic skin reaction with repeated or prolonged exposure consisting of redness, swelling and/or rash (urticaria).

### Medical Conditions Aggravated by Exposure

Could irritate an existing dermatitis or respiratory condition.

**IV. FIRST AID MEASURES**


- Skin contact:** Immediately flush skin with plenty of soap and water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse.
- Eye contact:** Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention if irritation persists. Avoid exposure to light sources.
- Inhalation:** Move affected person to fresh air. In case of asphyxia, initiate artificial respiration immediately. If breathing is difficult, give oxygen. Get medical attention immediately.
- Ingestion:** Ingestion is unlikely. However, if large quantities are swallowed, get medical attention do not induce vomiting. Never give anything by mouth to an unconscious person.

**Notes to Physician**

Allergic dermatitis in susceptible individuals may be delayed. It may appear after weeks or even months of frequent and prolonged contact.

**V. FIRE FIGHTING MEASURES**

- Flash Point: ~242 °C (467.6 °F)      Method Used: DIN 51758  
Upper Flammable Limit (UFL): NA      Lower Flammable Limit (LFL): NA  
Auto Ignition: >360 °C (DIN 51794)      Rate of Burning: NA

**NFPA Ratings**

- 0 = Minimal  
1 = Slight  
2 = Moderate  
3 = Serious  
4 = Severe

- General Fire Hazards:** Inhibitor depletion caused by exposure to heat, radiation or oxidizers can cause spontaneous polymerization generating heat and pressure.
- Hazardous Combustion Products:** Thermal decomposition products can include CO<sub>2</sub>, CO, NO<sub>x</sub> and smoke.
- Extinguishing Media:** Use water mist, dry chemical, carbon dioxide, or chemical foam. Avoid the use of a stream of water to control fire since frothing can occur.
- Fire Fighting Equipment/Instructions:** Wear full protective clothing, including helmet, self-contained positive-pressure or pressure-demand breathing apparatus, protective clothing and facemask. Move container from area if it can be done without risk. Cool containers with water spray. Do not use high-volume water jet. Avoid inhalation of material or combustion by-products.

**VI. ACCIDENTAL RELEASE MEASURES**

- Containment Procedures:** Stop the flow of material, if this is without risk. Ventilate contaminated area. Eliminate sources of ignition. Do not release material or contaminated water into drains, soil or surface waters.
- Clean-Up Procedures:** Wear appropriate protective equipment and clothing. Absorb spillage with non-combustible absorbent materials. Place all waste in an appropriate container for disposal.
- Evacuation Procedures:** Keep unnecessary personnel away.
- Special Procedures:** NA

**VII. HANDLING AND STORAGE**

- Handling Procedures:** Provide adequate ventilation. Avoid contact with skin and eyes. Do not breathe vapors or mist.
- Storage Procedures:** Store sealed in the original container at room temperature. Keep this material indoors in a cool, dry, well-ventilated place. Store out of direct sunlight or other light sources.
- Storage Temperature:** 0 °C – 35 °C / 32 °F – 95 °F

**VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION****Exposure Guidelines**

- A: General Product Information: No occupational exposure limits have been established.
- B: Component Analysis:

**Engineering Controls**

Ventilation must effectively remove any vapors.

# Material Safety Data Sheet

Page 3 of 5

Material Name: Accura<sup>®</sup> e-Stone<sup>™</sup>

## PERSONAL PROTECTIVE EQUIPMENT

Eyes/Face: Wear chemical goggles or face shield.

Skin: Use impervious gloves and apron.

Respiratory: If ventilation cannot effectively keep vapor concentrations below established limits, appropriate certified respiratory protection must be provided.

General: An eye wash fountain and safety shower are recommended.

## IX. PHYSICAL AND CHEMICAL PROPERTIES

Appearance ..... Green or peach

Odor ..... Acrylate

Physical State ..... Liquid

PH ..... NA

Vapor Pressure ..... < 2 Pa @ 20 °C

Flash Point ..... ~242 °C

Boiling Point ..... >200 °C

Viscosity ..... 200-300 cps at 30 °C

Solubility (H<sub>2</sub>O) ..... Insoluble @ 20°C (68 °F)

Specific Gravity ..... 1.1 g/cm<sup>3</sup> at 25 °C

Percent Volatile ..... NA

Molecular Weight ..... NA

## X. CHEMICAL STABILITY AND REACTIVITY

Chemical Stability: Stable under normal conditions of handling, use and transportation.

Conditions to Avoid: Avoid exposure to heat and light.

Incompatibility: Oxidizing materials, strong acids and strong bases.

Hazardous Decomposition: Thermal decomposition products can include CO<sub>2</sub>, CO, NO<sub>x</sub>, and smoke.

Hazardous Polymerization: Can occur, see sections III and V.

## XI. TOXICOLOGICAL INFORMATION

### Acute and Chronic Toxicity

A: General Product Information: No data available.

B: Component Analysis:

Component	LD <sub>50</sub> Oral	LD <sub>50</sub> Dermal
1,6-bis(2,3-epoxypropoxy)hexane (CAS# 16096-31-4)	> 8,500 mg/Kg (rats)	> 4,900 mg/Kg (rabbits)
Mixture containing triarylsulfonium salt	> 2,000 mg/Kg (rats)	> 2,000 mg/Kg (rabbits)

### Carcinogenicity

A: General Product Information: None.

B: Component Carcinogenicity: None of this product's components are listed by ACGIH, IARC, OSHA, NIOSH, or NTP.

## XII. ECOLOGICAL INFORMATION

### Ecotoxicity

A: General Product Information: The ecological assessment of this material is based on an evaluation of its components. This product is toxic to aquatic organisms and could cause long-term adverse effects in the aquatic environment.

B: Component Analysis - Ecotoxicity - Aquatic Toxicity:

Component	Data
1,6-bis(2,3-epoxypropoxy)hexane (CAS# 16096-31-4, EC# 240-260-4)	EC50/48h – 47 mg/l (daphnia) LC50/96h – 30 mg/l (leuciscus idus)
Mixture containing triarylsulfonium salt	EC50/24h – 4.4 mg/l (daphnia) EC50/48h – 0.68 mg/l (daphnia)

Environmental Fate: No information available for product.

# Material Safety Data Sheet

Material Name: Accura<sup>®</sup> e-Stone<sup>™</sup>

Page 4 of 5

## XIII. DISPOSAL CONSIDERATIONS

### Waste Disposal Instructions

Do not contaminate drains, soil or surface waters with the material or its container. Avoid disposal. Attempt to utilize product completely. Dispose of in compliance with all applicable regulations. Prior to disposal of unused material, consult an approved waste disposal operative to ensure regulatory compliance.

## XIV. TRANSPORT INFORMATION

	US DOT	RID/ADR	IMDG	IATA	IMO	Canada TDG
Shipping Name	Not Regulated					

## XV. REGULATORY INFORMATION

### US FEDERAL

TSCA:.....All materials are listed on the TSCA Inventory or are not subject to TSCA requirements

SARA 302 EHS List (40 CFR 355 Appendix A):.....None listed

SARA 313 (40 CFR 372.65):.....Antimony Compounds (category N010)

CERCLA (40 CFR 302.4):.....None listed

### STATE RIGHT-TO-KNOW STATUS

Component	CA Prop. 65	MI	NJ	PA	MA
None Listed	Not listed	Not listed	Not listed	Not listed	Not listed

### Component Analysis - Inventory

Component/CAS	EC #	EEC	CAN	TSCA	NLP
1,6-bis(2,3-epoxypropoxy)hexane (CAS# 16096-31-4)	240-260-4	EINECS	DSL	Yes	No
Mixture containing triarylsulfonium salt	Mixture	--	--	--	--
50% Propylene Carbonate (CAS# 203-572-1)	108-32-7	EINECS	DSL	Yes	No
50% Mixed triarylsulfonium hexafluoroantimonate salts (CAS# 89452-37-9, 71449-78-0)	403-500-0	EINECS	DSL	Yes	No

## XVI. ADDITIONAL INFORMATION

MSDS Creation Date:..... August 25, 2009

MSDS Revision #: ..... 01-A

MSDS Revision Date:..... December 15, 2011

Reason for Revision:..... Change Logo and Flash Point

For more information:..... [www.3dsystems.com](http://www.3dsystems.com)

800.793.3669 (Toll-free in the US GMT-07:00; N. America, Mon – Fri, 6:00 a.m. to 6 p.m.)

803.326.3900 (Outside the U.S. GMT-07:00; N. America, Mon – Fri, 6:00 a.m. to 6 p.m.)

+44 144-2282600 (Europe GMT+01:00; Mon – Fri, 08:00 a.m. - 17:00 p.m. MEZ)

DISCLAIMER OF LIABILITY: The following supersedes any provision in your company's forms, letters, and papers. 3D Systems, Inc. makes no warranty whether expressed or implied, including warranties of merchantability or of fitness for a particular purpose for this product. No statements or recommendations contained in the product literature are to be construed as inducements to infringe any relevant patent now or hereafter in existence. Under no circumstances shall 3D Systems, Inc. be liable for incidental, consequential, or other damages from alleged negligence, breach or warranty, strict liability or any other theory, arising out of the use or handling of this product. The sole liability of 3D Systems, Inc. for any claims arising out of the manufacture, use or sale of its products shall be for the buyer's purchase price.

© Copyright 2009-2011 by 3D Systems, Inc. All rights reserved. Subject to change without notice. SLA and Accura are registered trademarks of 3D Systems, Inc. The 3D logo and e-Stone are trademarks of 3D Systems, Inc.

# Material Safety Data Sheet

Page 5 of 5

Material Name: Accura<sup>®</sup> e-Stone<sup>™</sup>

---

## Key/Legend

ACGIH = American Conference of Governmental Industrial Hygienists

CAS = Chemical Abstracts Service

CERCLA = Comprehensive Environmental Response, Compensation, and Liability Act

CFR = Code of Federal Regulations

CPR = Controlled Products Regulations

DOT = Department of Transportation

DSL = Domestic Substances List

EINECS = European Inventory of Existing Commercial Chemical Substances

EPA = Environmental Protection Agency

IARC = International Agency for Research on Cancer

IATA = International Air Transport Association

IDL = Ingredients Disclosure List

mg/Kg = milligrams per Kilogram

mg/L = milligrams per Liter

mg/m<sup>3</sup> = milligrams per Cubic Meter

MSHA = Mine Safety and Health Administration

NA = Not Applicable or Not Available

NIOSH = National Institute for Occupational Safety and Health

NJTSR = New Jersey Trade Secret Registry

NTP = National Toxicology Program

OSHA = Occupational Safety and Health Administration

SARA = Superfund Amendments and Reauthorization Act

STEL = Short Term Exposure Limit

TDG = Transport Dangerous Goods

TSCA = Toxic Substances Control Act

WHMIS = Workplace Hazardous Materials Information System.